



Sicad s.p.A.

Via Caduti della Liberazione, 57  
21040 Uboldo (VA) – Italia  
Tel: +39 02 964121 Fax: +39 02 96412294  
Web: www.eurocel.it

## PRODUCT INFORMATION

# EUROCEL 700 RDA

### DESCRIPTION

Double sided adhesive tape.

### PRODUCT DATA

<b>Backing</b>	0.028 mm BOPP film; transparent
<b>Adhesive</b>	Synthetic rubber and resin; solventless
<b>Liner</b>	Double sided siliconized paper; brown

	Unit	Value	Method
<b>Total thickness (without Liner)</b>	mm	0.098	PSTC 133
<b>Adhesion to steel</b>	N/25mm	Int: 30 – Ext: 20	PSTC 101
<b>Tensile strength MD</b>	N/25mm	100	PSTC 131
<b>Elongation at break</b>	%	140	PSTC 131
<b>Temp. Resistance</b>	°C	60°C	=

### APPLICATION

Double sided tape suitable for fixing of photographs, pattern books and other light samples and easy jobs. Easy to use.

Features	Benefits	
Synthetic rubber and resins adhesive "solvent free"	✓ High tack and high adhesion level both sides	✓ Good adhesion on different surfaces
BOPP film backing	✓ High elongation	✓ Hand tearable *
*Feature available for few articles only		

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

DS001EN\_REV05\_700RDA

Società Italiana Cellophane Adesivo  
P.I. e C.F. IT 00220060123  
Iscrizione R.E.A. Varese n. 129175  
Reg. Imprese Varese n. 00220060123  
Capitale Sociale € 15.000.000 i.v.