

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

PRODUCT INFORMATION **EUROCEL MSK 6143**

DESCRIPTION

General purpose masking tape.

PRODUCT DATA

Backing	58 g/m² natural saturated crepe paper; white	
Adhesive	Natural rubber and resins solvent based	

	Unit	Value	Method
Total thickness	mm	0.120	PSTC 133
Adhesion to steel	N/25mm	4	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	7.5	PSTC 131
Temp. Resistance	°C	60°C (30 min)	

APPLICATION

General purpose masking tape, suitable for all kinds of simple painting jobs. Tape must be applied at room temperature. Recommended to remove within 36 hours.

Features	Benefits		
Natural rubber and resins solvent based adhesive	 ✓ Resistant to most common paints ✓ Good adhesion even on irregular ✓ surfaces residue 		
Saturated paper backing	 ✓ Well conformable to most shapes ✓ Compatible with most common paints and lacquers ✓ Removable without breaking ✓ Hand tearable 		

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.