



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL MSK 80

DESCRIPTION

Masking tape for automotive repair workshops.

PRODUCT DATA

Backing	58 g/m ² saturated crepe paper; yellow
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.135	PSTC 133
Adhesion to steel	N/25mm	4.5	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	9	PSTC 131
Temp. Resistance	°C	80°C (110°C x 30min)	=

APPLICATION

Masking tape suitable for applications requiring high temperature resistance.

Features	Benefits	
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none"> ✓ Good adhesion even on irregular surfaces ✓ High performance even in overlapping and with masking paper applied 	<ul style="list-style-type: none"> ✓ Heat resistant up to 110°C (30 min) ✓ Usable even for refinishing with Infra Red lamps ✓ Resistant to paint and lacquer thinners ✓ Easy removal without adhesive residue
Saturated paper backing	<ul style="list-style-type: none"> ✓ The yellow colour allows even shading, creating clear contrast with most frequent colours ✓ Well adaptable to most shapes 	<ul style="list-style-type: none"> ✓ Compatible with most common paints and lacquers ✓ Removable without breaking ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

MK006EN_REV04_MSK80

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.